Product sheet Matt non-woven 155 g/m²

Specifications:

Series: Matt non-woven 155 g/m²

Product description: Non-woven backing

Measurements: Width: \pm 50 cm \pm 19 inch

Roll Length: endless (determined by design)

Weight: $\pm 155 \text{ gr/m}^2 \pm 5 \text{ oz}$

Technical data: (typicals)

Size	Test procedure	Unit	Average
Area based size	DIN EN ISO 536	g/m²	150
Thickness	DIN EN ISO 534	μm	166
Buld density	DIN EN ISO 534	g/cm³	0,90
Breaking resistance lengthwise	DIN EN ISO 1924-2	N/15mm	117
Breaking resistance transversely	DIN EN ISO 1924-2	N/15mm	85
Elongation at break	DIN EN ISO 1924-2	%	3,3
Elongation at break transversely	DIN EN ISO 1924-2	%	7,4
Wet breakage resistance along	DIN ISO 3781	N/15mm	40
Wet expansion transversely	A 10-011 / 27 nach Fenchel	%	0,2
Transversely	DIN 53 107	sec	78
Smooth bottom	DIN 53 107	sec	16
White	DIN 53 145, T.1	%	89
Opacity	DIN 53 146	%	93

Application instruction:

Hanging instruction: Non reverse/straight Butt joint

Recommended BN Walls BK 10 for absorbing surfaces. BN Walls BK 30 for non-absorbing surfaces.

adhesive: Perfax - Universal Glue for Non-Woven Wallpaper.

Product features:

Resistant to: Soap

Not resistant to: Solvents like ketones; esters; aromatic hydrocarbons

Washability: Washable (with soft cloth, excluding microfibre cloth)

Services:

Warranty: All Items are free of workmanship and mechanical defects under normal use and service of five

years from date of delivery. This warranty applies only on professionally installed wallcoverings

as advised in BN Walls hanging instructions

Customized: Custom colours and design upon request, subject to minimum order quantity

Samples: A4 samples are available on request

Productsheet last revised: 01-02-2020

BN

BN Walls

The Netherlands

info@bnwalls.com bnwalls.com/professional